

SPECIFICATIONS

	PAGE NUMBER	HORSEPOWER (MAX/MIN)	CENTRILINE LENGTH	BEAM WIDTH	STERN WIDTH	AMIDSHIP DEPTH	BOW DEPTH	TRANSOM HEIGHT	STANDARD BOAT WEIGHT (APPROXIMATE - LBS.)	CAPACITY (LBS.)	FUEL TANK W/VOLUME (GALONS)	PERSONS (MAXIMUM)	HULL DESIGN	THICKNESS (FREEBOARD/BOTTOM)	TWIN HULL PLATE THICKNESS	PROTRAK™	SPORTRAK™	SEATS	SEAT BASES	CONSOLE (WITH STEERING)	LIVEWELL	WASHDOWN SYSTEM	LOCKABLE STORAGE
2150 Baron Magnum OB	13-14	275	21'10"	100"	98"	52.5"	56"	25"	2285	2150	★78	10	IPS2	.080/.100	.100	✓	–	3AR/1P	5	Twin✓/H	DPL	✓	✓
2150 Baron GS OB	13-14	275	21'10"	100"	100"	52.5"	56"	25"	2100	2150	★78	10	IPS2	.080/.100	.100	✓	✓	4	6	Twin✓/H	DPL	–	✓
1950 Tyee® Magnum OB	15-16	225	19'8"	98"	96.75"	45"	48"	25"	1900	2000	★50	9	IPS2	.080/.100	.100	✓	–	3AR/1P	5	Twin✓/H	DPL	✓	✓
1950 Tyee® GS OB	15-16	225	19'8"	98"	98"	45"	48"	25"	1735	2000	★50	9	IPS2	.080/.100	.100	✓	✓	4	6	Twin✓/H	DPL	–	✓
1850 Tyee® GS OB	17-18	175	18'6"	96"	95"	45"	48"	25"	1530	2000	★40	8	IPS2	.080/.100	.100	✓	✓	3	6	Twin✓/H	DPL	–	✓
1750 Tyee® GS OB	19-20	150	17'6"	93"	93"	43"	44"	25"	1375	1700	★27	7	IPS2	.080/.100	.100	✓	✓	3	6	Twin✓/H	DPL	–	✓
2025 Pro-V IFS/LE®	25-26	275	20'6"	97"	97"	38.5"	42"	25"	2110	2100	★55	7	IPS2	.080/.100	.100	✓	✓	3AR/1P	6	Twin✓/H	DPL	●	✓
2025 Pro-V IFS/SE®	25-26	275	20'6"	97"	97"	38.5"	42"	25"	2000	2100	★55	7	IPS2	.080/.100	.100	✓	✓	3AR/1P	6	Twin✓/H	DPL	●	✓
2025 Pro-V LE	25-26	275	20'6"	97"	97"	38.5"	42"	25"	1910	2100	★55	7	IPS2	.080/.100	.100	✓	✓	3AR/1P	6	Side✓/H	DPL	●	✓
2025 Pro-V SE	25-26	275	20'6"	97"	97"	38.5"	42"	25"	1900	2100	★55	7	IPS2	.080/.100	.100	✓	✓	3AR/1P	6	Side✓/H	DPL	●	✓
1900 Pro-V IFS/LE®	27-28	225	19'7"	95"	95"	37"	41"	25"	1905	1930	★45	6	IPS2	.080/.100	.100	✓	✓	3AR/1P	6	Twin✓/H	DPL	●	✓
1900 Pro-V IFS/SE®	27-28	225	19'7"	95"	95"	37"	41"	25"	1885	1930	★45	6	IPS2	.080/.100	.100	✓	✓	3AR/1P	6	Twin✓/H	DPL	●	✓
1900 Pro-V LE	27-28	225	19'7"	95"	95"	37"	41"	25"	1750	1955	★45	6	IPS2	.080/.100	.100	✓	✓	3AR/1P	6	Side✓/H	DPL	●	✓
1900 Pro-V SE	27-28	225	19'7"	95"	95"	37"	41"	25"	1730	1955	★45	6	IPS2	.080/.100	.100	✓	✓	3AR/1P	6	Side✓/H	DPL	●	✓
1800 Pro-V IFS/SE®	29-30	175	18'4"	93"	93"	35.5"	40"	25"	1620	1640	★40	6	IPS2	.080/.100	.100	✓	✓	2AR/1P	6	Twin(●/H)	DPL	–	✓
1800 Pro-V SE	29-30	175	18'4"	93"	93"	35.5"	40"	25"	1560	1640	★40	6	IPS2	.080/.100	.100	✓	✓	2AR/1P	6	Side(●/H)	DPL	–	✓
1800 Pro-V Tiller	29-30	90	18'4"	93"	93"	35.5"	40"	20"	1500	1640	★40	6	IPS2	.080/.100	.100	✓	✓	3AR	4	–	DPL	–	✓
Mr. Pike 18	33-34	150	18'2"	96"	95"	36"	40"	25"	1330	1625	32	6	IPS2	.063/.080	.080	✓	✓	3	6	Side(●/H)	DA/1R	–	✓
Mr. Pike 17	33-34	140	17'2"	93"	93"	35.5"	38"	25"(●20")	1285	1560	32	6	IPS2	.063/.080	.080	✓	✓	3	6	Side(●/H)	DA/1R	–	✓
Pro Angler 18 Tiller	35-36	90	18'2"	96"	95"	36"	40"	20"	1280	1625	32	6	IPS2	.063/.080	.080	✓	✓	3	4	–	DA/1R	–	✓
Pro Angler 17 Tiller	35-36	75	17'2"	93"	93"	35.5"	38"	20"	1210	1560	32	6	IPS2	.063/.080	.080	✓	✓	3	4	–	DA/1R	–	✓
2010 Pro Guide Tiller	37-38	115/175	20'2"	90"	89.5"	36.5"	39.5"	25"	1440	2000	★40	6	IPS2	.080/.100	.100	✓	✓	3	6	–	DA/1R	●	✓
2000 Alaskan DC	41-42	125	20'6"	90.5"	85"	35"	39"	20"	1275	2100	27	7	IPS	.080/.100	–	✓	✓	3	5	Twin(●/H)	AL	–	✓
2000 Alaskan SS	41-42	125	20'6"	90.5"	85"	35"	39"	20"	1200	2100	27	7	IPS	.080/.100	–	✓	✓	3	5	Side(●/H)	AL	–	✓
2000 Alaskan Tiller	41-42	115	20'6"	90.5"	85"	35"	39"	20"	1105	2100	27	7	IPS	.080/.100	–	✓	✓	3	4	–	AL	–	✓
1800 Alaskan SS	43-44	90	18'9"	83"	79"	33"	36"	20"	1030	1600	19	7	IPS	.080/.100	–	✓	✓	2	5	Side	AL	–	✓
1800 Alaskan Tiller	43-44	75	18'9"	83"	79"	33"	36"	20"	860	1600	19	7	IPS	.080/.100	–	✓	✓	2	4	–	AL	–	✓
1600 Alaskan SS	43-44	75	16'10"	81"	79"	33"	36"	20"	915	1350	19	6	IPS	.080/.100	–	✓	✓	2	4	Side	AL	–	✓
1600 Alaskan Tiller	43-44	60	16'10"	81"	79"	33"	36"	20"	860	1350	19	6	IPS	.080/.100	–	✓	✓	2	3	–	AL	–	✓
SSV-18 Tiller	43-44	60	18'4"	76"	70.5"	28.5"	33.5"	20"	460	1500	–	7	IPS	.063/.100	–	–	–	6B	–	●Side	–	–	–
SSV-16 Tiller	43-44	40	16'2"	72"	64.5"	28.5"	35"	15'/20"	340/350	1100/1200	–	5/6	IPS	.063/.080	–	–	–	6B	–	●Side	–	–	–
SSV-14 Tiller	43-44	35	14'2"	70"	64.5"	28.5"	35"	15'/20"	285/295	915/1020	–	4	IPS	.063/.063	–	–	–	6B	–	●Side	–	–	–
2000 Sport Angler	47-48	225	20'6"	97"	96"	42.5"	46"	25"	1600	2100	★50	6	IPS	.080/.100	.100	✓	✓	2	7	Twin(●/H)	AL	●	–
1800 Sport Angler	47-48	175	18'6"	97"	96"	42.5"	46"	25"	1460	1900	★41	6	IPS	.080/.100	.100	✓	✓	2	7	Twin(●/H)	AL	●	–
1700 Pro Sport	49-50	115	17'0"	88"	87.5"	37.25"	38.5"	20"	1200	1600	24	6	IPS	.063/.080	.080	✓	✓	3	6	Twin(●/H)	AL	–	✓
1800 Explorer Sport	51-52	150	18'1"	96"	95"	36.5"	42"	25"	1285	1600	32	6	IPS	.063/.080	.080	✓	✓	3	6	Twin(●/H)	DA	–	✓
1800 Explorer SS	51-52	150	18'1"	96"	95"	36.5"	42"	25"	1240	1600	32	6	IPS	.063/.080	.080	✓	✓	3	6	Side(●/H)	DA	–	✓
1800 Explorer Tiller	51-52	90	18'1"	96"	95"	36.5"	42"	20"	1185	1600	32	6	IPS	.063/.080	.080	✓	✓	3	4	–	DA	–	✓
1700 Explorer Sport	53-54	125	17'0"	91.5"	87"	34"	37"	20"	1150	1525	27	6	IPS	.063/.080	.080	✓	✓	3	6	Twin(●/H)	DA	–	✓
1700 Explorer SS	53-54	125	17'0"	91.5"	87"	34"	37"	20"	1080	1525	27	6	IPS	.063/.080	.080	✓	✓	3	6	Side(●/H)	DA	–	✓
1700 Explorer Tiller	53-54	75	17'0"	91.5"	87"	34"	37"	20"	1035	1525	27	6	IPS	.063/.080	.080	✓	✓	3	4	–	DA	–	✓
1600 Explorer SS	53-54	90	16'6"	86"	82.5"	34"	37"	20"	1035	1400	19	6	IPS	.063/.080	.080	✓	✓	2	6	Side(●/H)	DA	–	✓
1600 Explorer Tiller	53-54	60	16'6"	86"	82.5"	34"	37"	20"	960	1400	19	6	IPS	.063/.080	.080	✓	✓	2	3	–	DA	–	✓
1775 Classic Sport	55-56	90	17'3"	85"	82.5"	33.5"	35"	20"	1010	1450	19	6	IPS	.063/.080	.063	✓	✓	3	6	Twin(●/●)	AL	–	✓
1775 Classic SS	55-56	90	17'3"	85"	82.5"	33.5"	35"	20"	950	1450	19	6	IPS	.063/.080	.063	✓	✓	3	6	Side(●/●)	AL	–	✓
1775 Classic Tiller	55-56	75	17'3"	85"	82.5"	33.5"	35"	20"	840	1450	19	6	IPS	.063/.080	.063	✓	✓	3	4	–	AL	–	✓
1660 Classic Sport	55-56	75	16'3"	84"	82.5"	34"	36.5"	20"	900	1350	19	6	IPS	.063/.080	.063	✓	✓	2	6	Twin	AL	–	✓
1660 Classic SS	55-56	75	16'3"	84"	82.5"	34"	36.5"	20"	840	1350	19	6	IPS	.063/.080	.063	✓	✓	2	6	Side	AL	–	✓
1660 Classic Tiller	55-56	60	16'3"	84"	82.5"	34"	36.5"	20"	785	1350	19	6	IPS	.063/.080	.063	✓	✓	2	4	–	AL	–	✓
1625 Classic Sport	57-58	50	16'0"	76"	76"	33"	34.5"	20"	790	1250	–	5	IPS	.063/.063	–	✓	✓	2	6	Twin	AL	–	–
1625 Classic SS	57-58	40	16'0"	76"	76"	33"	34.5"	20"	665	1250	–	5	IPS	.063/.063	–	✓	✓	2	6	Side	AL	–	–
1625 Classic Tiller	57-58	40	16'0"	76"	76"	33"	34.5"	20"	630	1250	–	5	IPS	.063/.063	–	✓	✓	2	4	–	AL	–	–
1425 Classic SS	59	40	14'9"	76"	76"	31"	34.5"	20"	625	1080	–	4	IPS	.063/.063	–	✓	✓	2	6	Side	AL	–	–
1425 Classic Tiller	59	40	14'9"	76"	76"	31"	34.5"	20"	590	1080	–	4	IPS	.063/.063	–	✓	✓	2	4	–	AL	–	–
WC 16 DLX Tiller	60	30	16'2"	72"	63"	26.25"	29.5"	20"	425	1250	–	5	SVB	.063/.063	–	–	–	4B	–	–	AL	–	–
WC 16 Tiller	60	25	16'2"	72"	63"	26.25"	29.5"	15'/20"	325/335	1150	–	5	SVB	.063/.063	–	–	–	5B	–	–	–	–	–
WC 14 DLX Tiller	60	25	14'6"	69"	63"	26.25"	28.75"	20"	390	1000	–	4	SVB	.063/.063	–	–	–	3B	–	–	AL	–	–
WC 14 Tiller	60	25	14'6"	69"	63"	26.25"	28.75"	15'/20"	285/295	1000	–	4	SVB	.063/.063	–	–	–	4B	–	–	–	–	–
WC 12 Tiller	60	15	12'1"	60"	58"	23"	25.625"	15"	205	700	–	3	SVB	.063/.063	–	–	–	4B	–	–	–	–	–
A 14 Tiller	60	15	14'1"	61"	51.5"	21"	24.5"	15"	194	785	–	3	SVB	.063/.063	–	–	–	3B	–	–	–	–	–
A 12 Tiller	60	10	12'1"	60"	51.5"	21"	24.5"	15"	164	645	–	3	SVB	.063/.063	–	–	–	3B	–	–	–	–	–

SPECIFICATION LEGEND

- ✓ Standard Feature
- Optional Equipment

- Fuel System**
- ★ ProPlus Reserve Fuel System

- Hull Design**
- IPS IPS Bottom
 - IPS2 IPS2 Bottom
 - SVB Semi-V Bottom

- Seats**
- AR AirRide Pedestal Seats
 - P Power Pedestal Seats
 - B Perma-Ply Bench Seats

- Console (with steering)**
- Side Side Console
 - Twin Twin Consoles with walk-through windshield
 - H Hydraulic Steering
 - ◆ No-feedback Tilt Steering

- Livewells**
- AL Aerated Livewell
 - DA Dual Aerated Livewells