2006 SPECIFICATIONS

LUND BOAT COMPANY

	PAGE NUMBER	HORSEPOWER (MAXIMUM)	CENTERLINE LENGTH	BEAM WIDTH	STERN WIDTH	ADMIDSHIP DEPTH	BOW DEPTH	TRANSOM HEIGHT	STANDARD BOAT WEIGHT (APPROXIMATE-LBS.)	CAPACITY (LBS.)	FUEL TANK W/GAUGE (GALLONS)	PERSONS (MAXIMUM)	HULL DESIGN	THICKNESS (FREEBOARD/BOTTOM)	TWIN HULL THICKNESS PLATE	GUNWALE	SPORT TRAK	SEATS	SEAT BASES	CONSOLE (WITH STEERING)	LIVEWELL	WASHDOWN SYSTEM	LOCKABLE STORAGE	ROD STORAGE	BILGE PUMP	BATTERY HOLDER	INTERIOR LIGHTS	NAVIGATION LIGHTS	BOARDING LADDER	VINYL FLOOR	CARPETED FLOOR	CASTING PLATFORM	DECK MOUNTING PAD	STEP PADS	DECK RAILS	CLEATS	ALUMINUM KEELSONS	BOW EYE AND STERN HANDLES	BOW AND STERN EYES	PRO TRAK COVER	CANVAS TOP SET	BATTERY CHARGER	ACCESSORY BRACKETS
2150 Baron GS ITS®		300	21'10"	100"	98"	52.5"	56"	-	3390	2400	★78	10	IPS2	.080/.100	.100	PTG	-	3AR/1P	5	Twin DR	DPL	-	✓	✓L	✓2	✓4	5	✓	●	●	✓	✓	✓	✓	✓	4	-	-	✓	●	✓ST●CT	●	-
2150 Baron GS OB		250	21'10"	100"	98"	52.5"	56"	25"	2255	2150	★75	10	IPS2	.080/.100	.100	PTG	✓	3AR/1P	6	Twin✓H	DPL	-	✓	✓L	✓2	✓4	5	✓	●	●	✓	✓	✓	✓	✓	4	-	-	✓	●	✓ST●CT	●	✓2
1950 Tyee® GS ITS®		300	19'8"	98"	96.75"	45"	48"	-	2875	1725	★50	9	IPS2	.080/.100	.100	PTG	-	3AR/1P	5	Twin DR	DPL	-	✓	✓L	✓2	✓3	5	✓	●	●	✓	✓	✓	✓	✓	4	-	-	✓	●	✓ST●CT	●	-
1950 Tyee® GS OB		225	19'8"	98"	96.75"	45"	48"	25"	1875	2000	★50	9	IPS2	.080/.100	.100	PTG	✓	3AR/1P	6	Twin✓H	DPL	-	✓	✓L	✓2	✓3	5	✓	●	●	✓	✓	✓	✓	✓	4	-	-	✓	●	✓ST●CT	●	✓2
1850 Tyee® GS ITS®		260	18'6"	96"	95"	45"	48"	-	2710	1525	★41	8	IPS2	.080/.100	.100	PTG	-	2AR/1P	5	Twin DR	DPL	-	✓	✓L	✓2	✓3	5	✓	●	●	✓	✓	✓	✓	✓	4	-	-	✓	●	✓ST●CT	●	-
1850 Tyee® GS OB		200	18'6"	96"	95"	45"	48"	25"	1820	1900	★41	8	IPS2	.080/.100	.100	PTG	✓	2AR/1P	6	Twin✓H	DPL	-	✓	✓L	✓2	✓3	5	✓	●	●	✓	✓	✓	✓	✓	4	-	-	✓	●	✓ST●CT	●	✓2
2150 Baron Magnum OB		250	21'10"	100"	98"	52.5"	56"	25"	2285	2150	★78	10	IPS2	.080/.100	.100	PTG	-	3AR/1P	5	Twin✓H	DPL	✓	✓	✓L	✓2	✓4	5	✓	●	●	✓	✓	✓	✓	✓	4	-	-	✓	●	●ST●CT	●	-
1950 Tyee® Magnum OB		225	19'8"	98"	96.75"	45"	48"	25"	1900	2000	★50	9	IPS2	.080/.100	.100	PTG	-	3AR/1P	5	Twin✓H	DPL	✓	✓	✓L	✓2	✓3	5	✓	●	●	✓	✓	✓	✓	✓	4	-	-	✓	●	●ST●CT	●	-
1850 Tyee® Magnum OB		200	18'6"	96"	95"	45"	48"	25"	1800	1900	★41	8	IPS2	.080/.100	.100	PTG	-	2AR/1P	5	Twin✓H	DPL	✓	✓	✓L	✓2	✓3	5	✓	●	●	✓	✓	✓	✓	✓	4	-	-	✓	●	●ST●CT	●	-
2025 Pro-V Magnum LE		250	20'6"	97"	97"	38.5"	42"	25"	1910	2100	★55	7	IPS2	.080/.100	.100	PTG	✓	3AR/1P	6	Side✓H	DPL	✓	✓	✓L	✓2	✓4	5	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	●	●DT	●	✓2
2025 Pro-V Magnum SE		250	20'6"	97"	97"	38.5"	42"	25"	1900	2100	★55	7	IPS2	.080/.100	.100	PTG	✓	3AR/1P	6	Side✓H	DPL	✓	✓	✓L	✓2	✓4	5	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	●	●DT	●	✓2
2025 Pro-V Magnum IFS®		250	20'6"	97"	97"	38.5"	42"	25"	2000	2100	★55	7	IPS2	.080/.100	.100	PTG	✓	3AR/1P	6	Twin✓H	DPL	✓	✓	✓L	✓2	✓4	5	✓	-	●	✓	✓	✓	✓	✓	✓	4	-	-	✓	●	●CT	●	✓2
1900 Pro-V LE		225	19'7"	95"	95"	37"	41"	25"	1750	1955	★45	6	IPS2	.080/.100	.100	PTG	✓	3AR/1P	6	Side✓H	DPL	✓	✓	✓L	✓2	✓4	5	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	●	●DT	●	✓2
1900 Pro-V SE		225	19'7"	95"	95"	37"	41"	25"	1730	1955	★45	6	IPS2	.080/.100	.100	PTG	✓	3AR/1P	6	Side✓H	DPL	✓	✓	✓L	✓2	✓4	5	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	●	●DT	●	✓2
1900 Pro-V IFS®		225	19'7"	95"	95"	37"	41"	25"	1885	1930	★45	6	IPS2	.080/.100	.100	PTG	✓	3AR/1P	6	Twin✓H	DPL	✓	✓	✓L	✓2	✓4	5	✓	-	●	✓	✓	✓	✓	✓	✓	4	-	-	✓	●	●CT	●	✓2
1800 Pro-V SE		175	18'4"	93"	93"	35.5"	40"	25"(●20")	1560	1640	★40	6	IPS2	.080/.100	.100	PTG	✓	2AR/1P	6	Side(●H)	DPL	-	✓	✓L	✓2	✓4	5	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	●	●BT	●	✓2
1800 Pro-V Tiller		90	18'4"	93"	93"	35.5"	40"	20"	1500	1640	★40	6	IPS2	.080/.100	.100	PTG	✓	3AR	4	-	DPL	-	✓	✓L	✓2	✓4	5	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	●	●BT	●	✓2
1800 Pro-V IFS®		175	18'4"	93"	93"	35.5"	40"	25"(●20")	1620	1640	★40	6	IPS2	.080/.100	.100	PTG	✓	2AR/1P	6	Twin●(●H)	DPL	-	✓	✓L	✓2	✓4	5	✓	-	●	✓	✓	✓	✓	✓	✓	4	-	-	✓	●	●CT●BT	●	✓2
Mr. Pike 18		150	18'2"	96"	95"	36"	40"	25"(●20")	1330	1625	32	6	IPS	.063/.080	.080	PTG	✓	3	6	Side(●H)	DA/1R	-	✓	✓L	✓	✓3	4	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	●	●BT	●	✓2
Mr. Pike 17		140	17'2"	93"	93"	35.5"	38"	20"	1285	1560	32	6	IPS	.063/.080	.080	PTG	✓	3	6	Side(●H)	DA/1R	-	✓	✓L	✓	✓3	4	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	●	●BT	●	✓2
Mr. Pike 16		100	16'6"	89"	89"	34"	35.5"	20"	1215	1400	27	6	IPS	.063/.080	.080	PTG	✓	2	6	Side(●H)	DA/1R	-	✓	✓L	✓	✓3	4	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	●	●BT	●	✓2
Pro Angler 18		90	18'-2"	96"	95"	36"	40"	20"	1280	1625	32	6	IPS	.063/.080	.080	PTG	✓	3	4	-	DA/1R	-	✓	✓L	✓	✓3	4	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	●	●BT	●	✓2
Pro Angler 17		75	17'2"	93"	93"	35.5"	38"	20"	1210	1560	32	6	IPS	.063/.080	.080	PTG	✓	3	4	-	DA/1R	-	✓	✓L	✓	✓3	4	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	●	●BT	●	✓2
Pro Angler 16		75	16'6"	89"	89"	34"	35.5"	20"	1070	1400	27	6	IPS	.063/.080	.080	PTG	✓	2	4	-	DA/1R	-	✓	✓L	✓	✓3	4	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	●	●BT	●	✓2
2000 Alaskan DC		125	20'5"	89"	79-3/4"	32-1/4"	34-3/4"	20"	1185	2100	27	7	TLVB	.080/.100	-	STG	✓	3	5	Twin(●H)	AL	-	-	✓	✓	✓1	-	✓	-	✓	●	✓	✓	-	-	4	6	-	✓	-	●CT/ST	-	✓2
2000 Alaskan SS		125	20'5"	89"	79-3/4"	32-1/4"	34-3/4"	20"	1135	2100	27	7	TLVB	.080/.100	-	STG	✓	3	5	Side(●H)	AL	-	-	✓	✓	✓1	-	✓	-	✓	●	✓	✓	-	-	4	6	-	✓	-	●BT	-	✓2
2000 Alaskan		90	20'5"	89"	79-3/4"	32-1/4"	34-3/4"	20"	1080	2100	27	7	TLVB	.080/.100	-	STG	✓	3	4	-	AL	-	-	✓	✓	✓1	-	✓	-	✓	●	✓	✓	-	-	4	6	-	✓	-	●BT	-	✓2
1800 Alaskan SS		90	18'-9"	83"	79	33"	36"	20"	1030	1600	19	7	IPS	.080/.100	-	DTG	✓	2	5	Side	AL	-	-	✓	✓	✓1	-	✓	-	✓	-	-	✓	-	-	4	-	-	✓	●	●BT	-	✓2
1800 Alaskan		75	18'-9"	83"	79	33"	36"	20"	860	1600	19	7	IPS	.080/.100	-	DTG	✓	2	4	-	AL	-	-	✓	✓	✓1	-	✓	-	✓	-	-	✓	-	-	4	-	-	✓	●	●BT	-	✓2
1600 Alaskan SS		75	16'-10"	81-1/2"	79	33"	36"	20"	915	1350	19	6	IPS	.080/.100	-	DTG	✓	2	4	Side	AL	-	-	✓	✓	✓1	-	✓	-	✓	-	-	✓	-	-	4	-	-	✓	●	●BT	-	✓2
1600 Alaskan		60	16'-10"	81-1/2"	79	33"	36"	20"	860	1350	19	6	IPS	.080/.100	-	DTG	✓	2	3	-	AL	-	-	✓	✓	✓1	-	✓	-	✓	-	-	✓	-	-	4	-	-	✓	●	●BT	-	✓2
SSV-18		60	18'4"	76"	70-1/2"	28-1/2"	33.5"	20"	460	1500	-	7	IPS	.063/.100	-	TFBG	-	4B	-	●Side	-	-	-	-	-	-	-	●	-	-	-	-	-	-	-	4	✓	-	-	-	-	-	-
SSV-16		40	16'2"	72"	64-1/2"	28-1/2"	35"	15"/20"	340/350	1100/1200	-	5/6	IPS	.063/.080	-	TFBG	-	4B	-	●Side	-	-	-	-	-	-	-	●	-	-	-	-	-	-	-	4	✓	-	-	-	-	-	-
SSV-14		35	14'2"	70"	64-1/2"	28-1/2"	35"	15"/20"	285/295	915/1020	-	4	IPS	.063/.063	-	TFBG	-	4B	-	●Side	-	-	-	-	-	-	-	●	-	-	-	-	-	-	-	4	✓	-	-	-	-	-	-
2000 Fisherman ITS		300	19'11"	99"	99"	45"	46.5"	-	2725	1900	★55	10	IPS	.080/.100	.100	PTG	✓	4	5	Twin DR	DA	-	✓	✓L	✓	✓3	4	✓	●	●	✓	✓	✓	✓	✓	✓	4	-	-	✓	●	●CT/ST	●	-
2000 Fisherman OB		225	19'11"	99"	99"	45"	46.5"	25"	1730	2100	★55	10	IPS	.080/.100	.100	PTG	✓	4	6	Twin●(●H)	DA	-	✓	✓L	✓	✓3	5	✓	●	●	✓	✓	✓	✓	✓	✓	4	-	-	✓	●	●CT/ST	●	✓2
1800 Fisherman ITS		220	18'6"	96"	96"	44"	46"	-	2415	1625	★32	8	IPS	.080/.100	.100	PTG	✓	3	5	Twin DR	DA	-	✓	✓L	✓	✓3	4	✓	●	●	✓	✓	✓	✓	✓	✓	4	-	-	✓	●	●CT/ST	●	-
1800 Fisherman OB		175	18'6"	96"	96"	44"	46"	25"(●20")	1475	1900	★40	8	IPS	.080/.100	.100	PTG	✓	3	6	Twin●(●H)	DA	-	✓	✓L	✓	✓3	5	✓	●	●	✓	✓	✓	✓	✓	✓	4	-	-	✓	●	●CT/ST	●	✓2
1700 Fisherman		150	17'5"	93"	93"	41.5"	44"	20"(●25")	1300	1700	★27	7	IPS	.063/.080	.080	PTG	✓	3	6	Twin●(●H)	DA	-	✓	✓L	✓	✓3	5	✓	●	●	✓	✓	✓	✓	✓	✓	4	-	-	✓	●	●CT/ST	●	✓2
2000 Sport Angler		225	20'-5"	97"	96"	42.5"	46"	25"	1600	2100	★50	6	IPS	.080/.100	.100	DTG	✓	2	7	Twin●(●H)	AL	●	-	✓	✓	✓3	4	✓	●	✓	-	✓	✓	-	-	4	-	-	✓	●	●CT/ST	●	✓4
1800 Sport Angler		175	18'-5"	97"	96"	42.5"	46"	25"	1460	1900	★41	6	IPS	.080/.100	.100	DTG	✓	2	7	Twin●(●H)	AL	●	-	✓	✓	✓3	4	✓	●	✓	-	✓	✓	-	-	4	-	-	✓	●	●CT/ST	●	✓4
1700 Pro Sport		115	16'10"	89"	87.5"	37.25"	38.5"	20"	1200	1500	24	6	IPS	.063/.080	.080	PTG	✓	3	6	Twin●(●H)	AL	-	✓	✓L	✓	✓3	-	✓	●	●	✓	✓	✓	✓	✓	✓	4	-	-	✓	●	●CT/ST	●	✓2
1800 Explorer Sport		150	18'1"	96"	95"	36.5"	42"	20"(●25")	1285	1600	32	6	IPS	.063/.080	.080	PTG	✓	3	6	Twin●(●H)	DA	-	✓	✓L	✓	✓3	2	✓	-	●	✓	✓	✓	✓	-	-	4	-	-	✓	●	●CT/ST	●	✓2
1800 Explorer SS		150	18'1"	96"	95"	36.5"	42"	20"(●25")	1240	1600	32	6	IPS	.063/.080	.080	DTG	✓	3	6	Side(●H)	DA	-	✓	✓L	✓	✓3	2	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	●	●BT	●	✓2
1800 Explorer		90	18'1"	96"	95"	36.5"	42"	20"	1185	1600	32	6	IPS	.063/.080	.080	DTG	✓	3	4	-	DA	-	✓	✓L	✓	✓3	2	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	●	●BT	●	✓2
1700 Explorer Sport		125	17'0"	91.5"	87"	34"	37"	20"	1150	1525	27	6	IPS	.063/.080	.080	DTG	✓	3	6	Twin●(●H)	DA	-	✓	✓L	✓	✓3	2	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	●	●CT/ST	●	✓2
1700 Explorer SS		125	17'0"	91.5"	87"	34"	37"	20"	1080	1525	27	6	IPS	.063/.080	.080	DTG	✓	3	6	Side(●H)	DA	-	✓	✓L	✓	✓3	2	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	●	●BT	●	✓2
1700 Explorer		75	17'0"	91.5"	87"	34"	37"	20"	1035	1525	27	6	IPS	.063/.080	.080	DTG	✓	3	4	-	DA	-	✓	✓L	✓	✓3	2	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	●	●BT	●	✓2
1600 Explorer SS		90	16'6"	86"	82.5"	34"	37"	20"	1035	1400	19	6	IPS	.063/.080	.080	DTG	✓	2	6	Side(●H)	DA	-	✓	✓L	✓	✓2	2	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	●	●BT	●	✓2
1600 Explorer		60	16'6"	86"	82.5"	34"	37"	20"	960	1400	19	6	IPS	.063/.080	.080	DTG	✓	2	3	-	DA	-	✓	✓L	✓	✓2	2	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	●	●BT	●	✓2
1450 Rebel SS		50	14'-11"	75"	72-1/2"	30-1/2"	31"	20"	660	1135	-	4	IPS	.063/.080	-	TFBG	-	2	4	Side	AL	-	-	✓	✓	✓1	2	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	-	-	-	-
1450 Rebel		40	14'-11"	75"	72-1/2"	30-1/2"	31"	20"	615	1135	-	4	IPS	.063/.080	-	TFBG	-	2	3	-	AL	-	-	✓	✓	✓1	2	✓	-	●	✓	✓	✓	✓	✓	-	4	-	-	✓	-	-	-	-
WC-16 DLX		30	16'2"	72"	63"	26-1/4"	29-1/2"	20"	425	1150	-	5	SVB	.063/.063	-	TFBG	-	5B	-	-	AL	-	-	✓	✓	✓1	-	●	-	●	✓	✓	✓	✓	✓	-	4	5	✓	-	-	-	-	-
WC-16		25	16'2"	72"	63"	26-1/4"	29-1/2"	15"/20"	325/335	1000/1150	-	5	SVB	.063/.063	-	TFBG	-	5B	-	-	-	-	-	-	-	-	-	●	-	-	-	-	-	-	-	4	5	✓	-	-	-	-	-
WC-14 DLX		25	14'6"	69"	63"	26-1/4"	28-3/4"	20"	390	1000	-	4	SVB	.063/.063	-	TFBG	-	3B	-	-	AL	-	-	✓	✓	✓1	-	●	-	●	✓	-	-	-	-	4	5	✓	-	-	-	-	-
WC-14		25	14'6"	69"	63"	26-1/4"	28-3/4"	15"/20"	285/295	1000	-	4	SVB	.063/.063	-	TFBG	-	4B	-	-	-	-	-	-	-	-	-	●	-	-	-	-	-	-	-	4	5	✓	-	-	-	-	-
WC-12		15	12'1"	60"	58"	23"	25-5/8"	15"	205	700	-	3	SVB	.063/.063	-	TFBG	-	4B	-	-	-	-	-	-	-	-	-	●	-	-	-	-	-	-	-	4	3	✓	-	-	-	-	-
A-14		15	14'-1"	61"	51.5"	21"	24-1/2"	15"	180	780	-	4	SVB	.063/.063	-	TFBG	-	3B	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	4	3	✓	-	-	-	-	-
A-12		10	12'1"	60"	51.5"	21"	24-1/2"	15"	150	642	-	3	SVB	.063/.063	-	TFBG	-	3B	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	4	3	✓	-	-	-	-	-
1775 Classic Sport		90	17'-3"	85"	82.5	33.5	35	20"	1010	1450	19	6	IPS	.063/.080	.063	DTG	✓	3	6	Twin(●●)	AL	-	✓	✓L	✓	✓2	3	✓	-	✓	-	✓	✓	-	-	4	-	-	✓	●	●CT/ST	●	●
1775 Classic SS		90	17'-3"	85"	82.5	33.5	35	20"	950	1450	19	6	IPS	.063/.080	.063	DTG	✓	3	6	Side(●●)	AL	-	✓	✓L	✓	✓2	3	✓	-	✓	-	✓	✓	-	-	4	-	-	✓	●	●BT	●	●
1775 Classic		75	17'-3"	85"	82.5	33.5	35	20"	840	1450	19	6	IPS	.063/.080	.063	DTG	✓	3	4	-	AL	-	✓	✓L	✓	✓2	3	✓	-	✓	-	✓	✓	-	-	4	-	-	✓	●	●BT	●	●
1660 Classic Sport		75	16'-3"	84"	82.5	34	36.5	20"	900	1350	19	6	IPS	.063/.080	.063	DTG	✓	2	6	Twin	AL	-	✓	✓L	✓	✓2	3	✓	-	✓	-	✓	✓	-	-	4	-	-	✓	●	●CT/ST	●	●
1660 Classic SS		60	16'-3"	84"	82.5	34	36.5	20"	840	1350	19	6	IPS	.063/.080	.063	DTG	✓	2	6	Side	AL	-	✓	✓L	✓	✓2	3	✓	-	✓	-	✓	✓	-	-	4	-	-	✓	●	●BT	●	●
1660 Classic		60	16'-3"	84"	82.5	34	36.5	20"	785	1350	19	6	IPS	.063/.080	.063	DTG	✓	2	4	-	AL	-	✓	✓L	✓	✓2	3	✓	-	✓	-	✓	✓	-	-	4	-	-	✓	●	●BT	●	●
1625 Classic SS		40	16'-0"	76"	76"	33	34.5	20"	665	1250	-	5	IPS	.063/.063	-	DTG	✓	2	6	Side	AL	-	-	-	✓	✓2	-	✓	-	✓	-	✓	✓	-	-	4	-	-	✓	●	-	●	●
1625 Classic		40	16'-0"	76"	76"	33	34.5	20"	630	1250	-	5	IPS	.063/.063	-	DTG	✓	2	4	-	AL	-	-	-	✓	✓2	-	✓	-	✓	-	✓	✓	-	-	4	-	-	✓	●	-	●	●

✓ Standard Feature
● Optional Equipment
AR AirRide Pedestal Seats
P Power Pedestal Seats
B Perma-Ply Bench Seats

★ ProPlus Reserve Fuel System
L Lockable Rod Storage
AR Aerated Livewell
DA Dual Aerated Livewells
PL ProLong Livewell
DPL Dual ProLong Livewells
R Recirculating Livewell Pump (Mr. Pike has one recirculating pump)
♦ No-feedback Tilt Steering

DR Dual Rotary Tilt Steering
Twin Twin Consoles with Walk-thru Windshield
Side Side Console
Side- Side Console without Steering

CT Complete Top Set - Includes Top, Sides, Bows, Stern Cover, Walkway Curtain, Boot, and Tonneau
ST Sun Top Set - Includes Top, Bows, Walkway Curtain, Boot, and Tonneau
DT Dodger Top
BT Bimini Top
PTG Pro Trak Gunwale
STG Sport Trak Gunwale
DTG Dual Trak Gunwale
TFBG Traditional Fish Boat Gunwale
SVB Semi-V Bottom
TLVB True Lund V Bottom
IPS IPS Bottom

IPS2 IPS2 Bottom